

# Performance Data Sheet

Model: AP200

Use Replacement Cartridge AP217

The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI Standard 42.



System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of substances listed below.

Capacity 2000 Gallons (7570 Liters) Contaminant Reduction Determined by NSF testing.

Contaminant Reduction	Average Influent	NSF specified Challenge Concentration	Avg % Reduction	Average Product Water Concentration	Max Permissible Product Water Concentration	NSF Reduction Requirements	NSF Test Report
Chlorine Taste and Odor	2.0 mg/L	2.0 mg/L ± 10%	68.0%	0.64 mg/L	N/A	≥ 50%	J-00029568

Application Guidelines/Water Supply Parameters	
Service Flow	1.75 gpm (6.6 lpm)
Water Supply	Potable Water
Water Pressure	25 -125 psi (172 – 862 kPa)
Water Temperature	40° F - 100° F (4.4° C - 38° C)

It is essential that the manufacturer's recommended installation, maintenance and filter replacement requirements be carried out for the product to perform as advertised. See Installation Manual for Warranty information.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

Replacement Cartridge: **AP217**. For estimated costs of replacement elements please call 1-800-222-7880 or visit our website at [www.3Mpurification.com](http://www.3Mpurification.com)

⚠ WARNING
<p>To reduce the risk associated with ingestion of contaminants:</p> <ul style="list-style-type: none"> <li>Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before and after the system.</li> </ul>

CAUTION
<p>To reduce the risk associated with property damage due to water leakage:</p> <ul style="list-style-type: none"> <li><b>Read and follow</b> Use Instructions before installation and use of this system.</li> <li>Installation and use <b>MUST</b> comply with all state and local plumbing codes.</li> <li><b>Do not</b> install if water pressure exceeds 125 psi (862 kPa). If your water pressure exceeds 80 psi, you <b>must</b> install a pressure limiting valve. Contact a plumbing professional if you are uncertain how to check your water pressure.</li> <li><b>Do not</b> install where water hammer conditions may occur. If water hammer conditions exist you <b>must</b> install a water hammer arrester. Contact a plumbing professional if you uncertain how to check for this condition.</li> <li><b>Do not</b> install on hot water supply lines. The maximum operating water temperature of this filter system is 100° F (38° C).</li> <li><b>Protect filter from freezing.</b> Drain filter when temperatures drop below 40°F (4.4°C).</li> <li>The disposable filter cartridge <b>must</b> be replaced every <b>6</b> months, at the rated capacity or sooner, if a noticeable reduction in flow rate occurs.</li> </ul>

Parts and service available from:



**3M Purification Inc.**  
 400 Research Parkway  
 Meriden, CT 06450, U.S.A.  
 Tel (800) 222-7880  
 (203) 237-5541  
 Fax (203) 238-8701  
[www.3Mpurification.com](http://www.3Mpurification.com)

3M is a trademark of 3M Company.  
 © 2011 3M Company. All rights reserved.  
 NSF is a trademark of NSF International  
 INSTR2182 1111