

Cast Deckmount Sink Faucets 8" Centers

TECK®
COMMERCIAL

DELTA®

Specification: (example)

- **HEAVY DUTY CAST BRASS** sink faucet
 - 203mm (8") center two handle
 - Polished chrome plated finish
 - **BRASS** swing spout or 3/8" IPS **BRASS PIPE** Rigid/Swivel Gooseneck Spout
 - Metal hold-down package
 - Color indexed metal handles with vandal resistant screws
 - **CER-TECK®** 1/4 turn ceramic structures
- and ... with ... (add spout required)
 with ... (add outlet required)
 with ... (add handle required)
 with ... (add suffix **-LS** if required – See Back Page)
 with ... (add suffix **-TI** if required – See Back Page)

26C3944



26C3133

Engineer/Architect Approval

Model Specified:

Approval:

Date:

DESCRIPTION	PRODUCT NO.
CAST Deckmount	26C3



SPOUT	OUTLET	HANDLE
0 ☐	0 ☐	0 ☐
1 203mm (8") Wallform (S2) Swing Spout (2) ☐	1 ☐	1 Five Flute Handles ☐
2 203mm (8") Tubular (S5) Swing Spout (2) ☐	2 Vandal Resistant 1.5 gpm (5.7 L/min.) Laminar with Agion® Antimicrobial ☐	2 102mm (4") Hooded Blade Handles (5) ☐
3 ☐	3 Vandal Resistant 1.5 gpm (5.7 L/min.) Flow Control Aerator ☐	3 76mm (3") Hooded Lever Handles (5) ☐
4 ☐	4 Standard 1.5 gpm (5.7 L/min.) Flow Control Aerator ☐	4 102mm (4") Blade Handles, Sanitary Hoods (5) ☐
5 ☐	5 Vandal Resistant Non-Aerating Spray Outlet 0.5 gpm (1.9 L/min.) ☐	5 152mm (6") Wrist Handles, Sanitary Hoods ☐
6 ☐	6 ☐	6 ☐
7 ☐	7 Smooth End, Laminar Flow Control in Base of Gooseneck Spout 1.0 gpm (3.8 L/min.) (3) ☐	7 ☐
8 ☐	8 ☐	8 ☐
9 Heavy Duty 152mm (6") Bend Rigid/Swivel (R4) Gooseneck Spout (1) (4) ☐	9 ☐	9 ☐

(1) Available **Optional Rigid/Swivel Spouts**. These spouts can ONLY be added to **SPOUT Option No. 9**. Note: Use this page front and back as a product submittal sheet. Flow Rates are at 60 PSI.
 (2) Available **Optional Swing Spouts**. These spouts can ONLY be added to **SPOUT Option No. 2**. Refer to www.specselect.com for individual models.
 (3) This outlet can ONLY be added to **SPOUT Option No. 9**. (4) 120° Limited Swing Spout available. Add Suffix **-LS**. (5) H/C Temperature Indicator Available. Add Suffix **-TI**.
 Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

DSP-26C Rev. A



TECK[®]
COMMERCIAL

Cast Deckmount Sink Faucets 8" Centers


Approvals:

- CSA certified
- Complies to ASME A112.18.1/CSA B125.1
- Handles No. 2, 3, 4, and 5
Indicates compliance to ICC/ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulations


(Contact Delta Representative for State and/or Local Approvals.)

HANDLE TEMPERATURE INDICATORS

- ☐ Add suffix **"-TI"** to Product Number for handle temperature indicators "H" (red), "C" (blue).
Available on handle options 2, 3 or 4 only.



FLOW RATE vs PRESSURE



FOR OPTIONAL RIGID/SWIVEL & LIMITED SWING SPOUTS

See DSP-R/S for detailed specification


FOR OPTIONAL SWING SPOUTS

See DSP-S/S for detailed specification

Note: Measurements may vary
± 6mm (0.25")

Refer to www.specselect.com for individual models.



FRONT VIEW




GOOSENECK SPOUT

Outlets #2, 3, 4 & 5

Outlet #7



SWING SPOUT



LIMITED SWING GOOSENECK

- ☐ Add suffix **"-LS"** to Product Number for 120° Limited Swing

OUTLET NO.	"D"	
	mm	in.
2	18	0.69
3	18	0.69
4	17	0.67
5	18	0.69

GOOSENECK SPOUT ASSEMBLY #9

SPOUT/OUTLET	"A"		"C"		"L"	
	mm	in.	mm	in.	mm	in.
Gooseneck-Standard (R4) for outlets #2, 3, 4 & 5	152	6	124	4.9	146	5.8
Gooseneck-Standard (R4) for outlet #7	152	6	117	4.6	152	6.0

SWING SPOUT ASSEMBLIES

SPOUT NO.	SPOUT TYPE	"A"		"C"		"L"	
		mm	in.	mm	in.	mm	in.
1	8" Wallform Spout (52)	206	8.1	15	0.6	130	5.1
2	8" Tubular Spout (55)	185	7.3	41	1.6	147	5.8

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.