

**MATERIAL SAFETY DATA SHEET**

REVISION DATE: 06-15-2012

SUPERSEDES: 08-14-2009

**SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****COMPANY INFORMATION**

H.B. Fuller Construction Products Inc.  
1105 S. Frontenac Street  
Aurora, IL 60504  
Phone: 1-800-552-6225

Medical Emergency Phone Number (24 Hours): 1-888-853-1758  
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**PRODUCT INFORMATION**

PRODUCT NUMBER: FOSTER 32-19  
PRODUCT DESCRIPTION: Sealant  
PRODUCT IDENTIFIER: 802281PM

**SECTION 2: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

PHYSICAL STATE: Liquid  
COLOR: Gray  
ODOR: Mild Sweet  
Cancer hazard.

**POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY**

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

**LONG-TERM (CHRONIC) HEALTH EFFECTS**

TARGET ORGAN(S): Lungs

**REGULATED CARCINOGEN STATUS:**

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens.

Titanium dioxide

Crystalline silica

Cristobalite

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS #	PERCENT
Calcium carbonate	471-34-1	10 - 30

**MATERIAL SAFETY DATA SHEET**

Kaolin clay	1332-58-7	10 - 30
Titanium dioxide	13463-67-7	1 - 5
Crystalline silica	14808-60-7	0.1 - 1
Cristobalite	14464-46-1	0.1 - 1

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

**SECTION 4: FIRST AID MEASURES**

**IF IN EYES:** Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

**IF ON SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**IF VAPORS INHALED:** Remove to fresh air. Call a physician if symptoms persist.

**IF SWALLOWED:** Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

**SECTION 5: FIRE FIGHTING MEASURES**

<b>FLASH POINT:</b>	Non flammable
<b>AUTOIGNITION TEMPERATURE:</b>	Not established
<b>LOWER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>UPPER EXPLOSIVE LIMIT (% in air):</b>	Not established
<b>EXTINGUISHING MEDIA:</b>	Use water spray, foam, dry chemical or carbon dioxide.
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS:</b>	There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.
<b>SPECIAL FIRE FIGHTING INSTRUCTIONS:</b>	Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
<b>HAZARDOUS COMBUSTION PRODUCTS:</b>	Carbon dioxide, Carbon monoxide

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPECIAL PROTECTION:** No adverse health effects expected from the clean-up of spilled material. Follow personal protective equipment recommendations found in Section 8 of this MSDS.

**CLEAN-UP:** Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds, or water systems.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

**SECTION 7: HANDLING AND STORAGE**

**Handling:** No special handling instructions due to toxicity.

**Storage:** Store in a cool, dry place.  
Consult the Technical Data Sheet for specific storage instructions.

## MATERIAL SAFETY DATA SHEET

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**EYE PROTECTION:** Wear safety glasses when handling this product.  
**SKIN PROTECTION:** Avoid skin contact by wearing chemically resistant gloves.  
**GLOVES:** Not normally required. Use nitrile gloves if conditions warrant.  
**RESPIRATORY PROTECTION:** Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).  
**VENTILATION:** Use local exhaust ventilation or other engineering controls to minimize exposures.

### EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL
Calcium carbonate	Not established	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Kaolin clay	2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Titanium dioxide	10 mg/m <sup>3</sup> TWA	15 mg/m <sup>3</sup> TWA (total dust)
Crystalline silica	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	((250)/(%SiO <sub>2</sub> + 5) mppcf TWA (respirable)); ((10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (respirable)); ((30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA (total dust))
Cristobalite	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	Not established

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid  
**COLOR:** Gray  
**ODOR:** Mild Sweet  
**ODOR THRESHOLD:** Not established  
**WEIGHT PER GALLON (lbs.):** 11.70  
**SPECIFIC GRAVITY:** 1.400  
**SOLIDS (% by weight):** 69.0

**pH:** Not established  
**FLASH POINT:** Non flammable  
**BOILING POINT (deg. C):** Not established  
**FREEZING/MELTING POINT (deg. C):** Not established  
**VAPOR PRESSURE (mm Hg):** Not established  
**VAPOR DENSITY:** Not established  
**EVAPORATION RATE:** Not established  
**OCTANOL/WATER COEFFICIENT:** Not established  
**VOC, weight percent** 1.00  
**VOC, EPA Method 24, less water and exempt solvents** 24g/liter of material  
 (theoretically determined)

## MATERIAL SAFETY DATA SHEET

### SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** Stable under normal conditions.  
**CHEMICAL INCOMPATIBILITY:** Not established  
**HAZARDOUS POLYMERIZATION:** Will not occur.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide

### SECTION 11: TOXICOLOGICAL INFORMATION

COMPONENT	LD50/LC50
Calcium carbonate	Oral LD50 Rat = 6,450 mg/kg
Kaolin clay	Not established
Titanium dioxide	Not established
Crystalline silica	Not established
Cristobalite	Not established

**TOXICOLOGY SUMMARY:** No additional health information available.

### SECTION 12: ECOLOGICAL INFORMATION

**OVERVIEW:** No ecological information available

### SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

### SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

**DOT:** NOT REGULATED  
**IATA:** NOT REGULATED

### SECTION 15: REGULATORY INFORMATION

#### INVENTORY STATUS

**U.S. EPA TSCA:** This product is in compliance with the Toxic Substances Control Act's Inventory requirements.  
**CANADIAN CEPA DSL:** The components of this product are included on the DSL or are exempt from DSL requirements.  
**EUROPEAN EINECS:** As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

#### FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

Chemical Name	CAS#	%

**MATERIAL SAFETY DATA SHEET**

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A

**STATE REPORTING**

Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

Unless listed below, this product does not contain known levels of any chemical known to the State of California to cause cancer or reproductive harm.

Chemical Name/List	CAS	Percent
Titanium dioxide (Carcinogen)	13463-67-7	1 - 5
Quartz (Carcinogen)	14808-60-7	0.1 - 1
Carbon black (Carcinogen)	1333-86-4	0.01 - 0.1
Acetaldehyde (Carcinogen)	75-07-0	0.001 - 0.01
Formaldehyde (Carcinogen)	50-00-0	0.001 - 0.01
1,4-Dioxane (Carcinogen)	123-91-1	< 10 ppm
Ethyl acrylate (Carcinogen)	140-88-5	< 10 ppm
Methanol (Developmental toxin)	67-56-1	< 10 ppm

**SECTION 16: ADDITIONAL INFORMATION**

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department

Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.