

# HOLDRITE®

CONVERTING MAKESHIFT METHODS INTO ENGINEERED SOLUTIONS<sup>SM</sup>

## HOLDRITE STOUT BRACKET®



2-eared 90s



Vertical Mid-Span



3-eared 90s



Patent Pending

Compatible  
With Metal &  
Wood Studs

Positioning  
Tabs for Wood  
Studs

Telescoping  
Design

Compatible  
with Copper,  
CPVC and PEX

Wide bracket/tabs  
for extra rigidity



#SB3, #SB4

### HOLDRITE STOUT BRACKET SUPPORTS VARIOUS COMPONENTS



| Beam Span | Model # | Center Pt. Load (lbs.) |
|-----------|---------|------------------------|
| 10-1/4"   | SB3     | 863                    |
| 14-1/2"   | SB3     | 480                    |
| 16"       | SB3     | 322                    |
| 16"       | SB4     | 550                    |
| 22-1/2"   | SB4     | 271                    |
| 24"       | SB4     | 228                    |

(800) 321-0316 • [www.holdrite.com](http://www.holdrite.com)

# HOLDRITE STOUT BRACKET®

Numerous clamps and fittings integrate onto multiple sides of the Stout Bracket for vertical and horizontal positions

Multi-purpose galvanized steel bracket supports various application solutions

Telescoping design supports Copper, PEX, CPVC, & other piping

Unique tab design allows versatile installations

#SB1,  
#SB2



| Beam Span | Model # | Center Pt. Load (lbs.) |
|-----------|---------|------------------------|
| 10"       | SB1     | 400                    |
| 14-1/2"   | SB1     | 164                    |
| 18"       | SB1     | 104                    |
| 18"       | SB2     | 158                    |
| 22-1/2"   | SB2     | 124                    |
| 24"       | SB2     | 65                     |



Patent Pending

## HOLDRITE STOUT BRACKET®

| MODEL#   | DESCRIPTION                                                                                                                                                             | BOX QTY |
|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| SB3      | Wide telescoping galvanized steel bracket extends 10-1/4" – 18-1/2". Ideal for pipe support for shower head (2-eared or 3-eared 90s), tub spout, and vertical mid-span. | 50      |
| SB4      | Wide telescoping galvanized steel bracket extends 13-1/4" – 25-1/2". Ideal for pipe support for shower head (2-eared or 3-eared 90s), tub spout, and vertical mid-span. | 50      |
| SB1      | Telescoping galvanized steel bracket extends 10" – 18". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support.                                  | 50      |
| SB2      | Telescoping galvanized steel bracket extends 13" – 25". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support.                                  | 50      |
| SB1S     | Telescoping galvanized steel bracket extends 10" – 18". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support. Includes two screws.             | 50      |
| SB2S     | Telescoping galvanized steel bracket extends 13" – 25". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support. Includes two screws.             | 50      |
| SB1-2502 | Telescoping galvanized steel bracket extends 10" – 18", (2) #250 variable closure clamps, and (4) screws.                                                               | 25      |
| SB2-2502 | Telescoping galvanized steel bracket extends 13" – 25", (2) #250 variable closure clamps, and (4) screws.                                                               | 25      |

## HOLDRITE® CLAMPS

| MODEL#  | DESCRIPTION                                                                                                                                                      | BOX QTY |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| 250     | Variable closure clamp mounts to Stout Brackets & EZ-Strut trapeze brackets. Noise & vibration isolation clamp supports up to 1" CTS. Framework rated UL 94 V-2. | 50      |
| 255     | Variable closure clamp mounts to Stout Brackets. Noise & vibration isolation clamp supports up to 1" CTS. Framework rated UL 94 V-2.                             | 50      |
| 280     | Variable closure clamp mounts to Stout Brackets & EZ-Strut trapeze brackets. Noise & vibration isolation clamp supports 1"-2" CTS. Framework rated UL 94 V-2.    | 50      |
| 285     | Variable closure clamp mounts to Stout Brackets. Noise & vibration isolation clamp supports 1"-2" CTS. Framework rated UL 94 V-2.                                | 50      |
| 211     | Half moon clamp mounts to all Stout Brackets. Clamps are glueable for 1/2" CTS CPVC tubing. Rated UL 94 V-0.                                                     | 100     |
| 212     | Half moon clamp mounts to all Stout Brackets. Clamps are glueable for 3/4" CTS CPVC tubing. Rated UL 94 V-0.                                                     | 100     |
| 221-226 | Suspension clamp 1/2" to 2" CTS. (#221=.19; #222=.23; #223=.68; #224=.86; #225=1.00; #226=1.18)                                                                  | 25-100  |
| 231-236 | Standard clamp 1/2" to 2" CTS. (#231=.19; #232=.23; #233=.68; #234=.76; #235=.82; #236=1.01)                                                                     | 25-100  |
| 201     | Quick closing clamp mounts to SB1 and SB2 series Stout Brackets. Supports 1/2" CTS tubing. Rated UL 94 V-2.                                                      | 50      |
| 202     | Quick closing clamp mounts to SB1 and SB2 series Stout Brackets. Supports 3/4" CTS tubing. Rated UL 94 V-2.                                                      | 50      |

(800) 321-0316 • [www.holdrite.com](http://www.holdrite.com)

© 2011 HOLDRITE. All Rights Reserved.

#LT19 - 6/11