

HOLDRITE®

CONVERTING MAKESHIFT METHODS INTO ENGINEERED SOLUTIONSSM

HOLDRITE STOUT BRACKET®



2-eared 90s



Vertical Mid-Span



3-eared 90s



Patent Pending

Compatible
With Metal &
Wood Studs

Positioning
Tabs for Wood
Studs

Telescoping
Design

Compatible
with Copper,
CPVC and PEX

Wide bracket/tabs
for extra rigidity



#SB3, #SB4

HOLDRITE STOUT BRACKET SUPPORTS VARIOUS COMPONENTS



Beam Span	Model #	Center Pt. Load (lbs.)
10-1/4"	SB3	863
14-1/2"	SB3	480
16"	SB3	322
16"	SB4	550
22-1/2"	SB4	271
24"	SB4	228

(800) 321-0316 • www.holdrite.com

HOLDRITE STOUT BRACKET®

Numerous clamps and fittings integrate onto multiple sides of the Stout Bracket for vertical and horizontal positions

Multi-purpose galvanized steel bracket supports various application solutions

Telescoping design supports Copper, PEX, CPVC, & other piping

Unique tab design allows versatile installations

#SB1,
#SB2



Beam Span	Model #	Center Pt. Load (lbs.)
10"	SB1	400
14-1/2"	SB1	164
18"	SB1	104
18"	SB2	158
22-1/2"	SB2	124
24"	SB2	65



Patent Pending

HOLDRITE STOUT BRACKET®

MODEL#	DESCRIPTION	BOX QTY
SB3	Wide telescoping galvanized steel bracket extends 10-1/4" – 18-1/2". Ideal for pipe support for shower head (2-eared or 3-eared 90s), tub spout, and vertical mid-span.	50
SB4	Wide telescoping galvanized steel bracket extends 13-1/4" – 25-1/2". Ideal for pipe support for shower head (2-eared or 3-eared 90s), tub spout, and vertical mid-span.	50
SB1	Telescoping galvanized steel bracket extends 10" – 18". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support.	50
SB2	Telescoping galvanized steel bracket extends 13" – 25". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support.	50
SB1S	Telescoping galvanized steel bracket extends 10" – 18". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support. Includes two screws.	50
SB2S	Telescoping galvanized steel bracket extends 13" – 25". Ideal for lavatory, water closet, vertical/horizontal, and tub/shower support. Includes two screws.	50
SB1-2502	Telescoping galvanized steel bracket extends 10" – 18", (2) #250 variable closure clamps, and (4) screws.	25
SB2-2502	Telescoping galvanized steel bracket extends 13" – 25", (2) #250 variable closure clamps, and (4) screws.	25

HOLDRITE® CLAMPS

MODEL#	DESCRIPTION	BOX QTY
250	Variable closure clamp mounts to Stout Brackets & EZ-Strut trapeze brackets. Noise & vibration isolation clamp supports up to 1" CTS. Framework rated UL 94 V-2.	50
255	Variable closure clamp mounts to Stout Brackets. Noise & vibration isolation clamp supports up to 1" CTS. Framework rated UL 94 V-2.	50
280	Variable closure clamp mounts to Stout Brackets & EZ-Strut trapeze brackets. Noise & vibration isolation clamp supports 1"-2" CTS. Framework rated UL 94 V-2.	50
285	Variable closure clamp mounts to Stout Brackets. Noise & vibration isolation clamp supports 1"-2" CTS. Framework rated UL 94 V-2.	50
211	Half moon clamp mounts to all Stout Brackets. Clamps are glueable for 1/2" CTS CPVC tubing. Rated UL 94 V-0.	100
212	Half moon clamp mounts to all Stout Brackets. Clamps are glueable for 3/4" CTS CPVC tubing. Rated UL 94 V-0.	100
221-226	Suspension clamp 1/2" to 2" CTS. (#221=.19; #222=.23; #223=.68; #224=.86; #225=1.00; #226=1.18)	25-100
231-236	Standard clamp 1/2" to 2" CTS. (#231=.19; #232=.23; #233=.68; #234=.76; #235=.82; #236=1.01)	25-100
201	Quick closing clamp mounts to SB1 and SB2 series Stout Brackets. Supports 1/2" CTS tubing. Rated UL 94 V-2.	50
202	Quick closing clamp mounts to SB1 and SB2 series Stout Brackets. Supports 3/4" CTS tubing. Rated UL 94 V-2.	50

(800) 321-0316 • www.holdrite.com

© 2011 HOLDRITE. All Rights Reserved.

#LT19 - 6/11