

Print Page

SHARE



Previous

 | Item 2 Of 6 |

Next



TH8110U1003/U

Premier White® universal programmable thermostat with 1 heat/1 cool stages

Find Equivalent or Replacement Products.

Product Info

Literature

Accessories & Replacement Parts

Overview

VisionPRO® 8000 has responsive programming for optimal comfort and energy savings. It offers you features like touch screen interaction, a real-time clock, and a backlit display. If you value comfort, choose VisionPRO and enjoy it for years to come.

Product Specifications

Hazmat Information	UN 3091 Lithium metal batteries packed in/with equipment
Application	Heat/Cool or Heat Pump without Auxiliary Heat
Dimensions (in.)	4 9/16 in. high x 6 in. wide x 1 1/4 in. deep
Dimensions (mm)	116 mm high x 152 mm wide x 32 mm deep
Comments	Selectable: Programmable or Non-Programmable; Selectable; Heat Only or Cool Only
Item Type	Product
Mounting	Horizontal
Electrical Ratings	20 to 30 Vac or 750 mV
Frequency	50 Hz; 60 Hz
Stages	Up to 1 Heat/1 Cool
Operating Humidity Range (% RH)	5 to 90% RH, non-condensing
Switch Positions (System)	HEAT-OFF-COOL-AUTO
Switch Positions (Fan)	AUTO-ON-CIRC
Sensor Element	Thermistor
Differential Temperature (F)	± 1 F
Differential Temperature (C)	±0.5 C
Color	Premier White®
Programmability	7 Day Multiple Day Programming or Non-Programmable
Power Method	Battery or Hardwired
Terminal Designations	R, RC, C, W (O/B), Y, G, S1, S2
Display Size	10 sq in.
Changeover	Auto/Manual Selectable
Setting Temperature Range (F)	Heat: 40 F to 90 F; Cool: 50 F to 99 F
Setting Temperature Range (C)	Heat: 4.5 C to 32 C; Cool: 10 C to 37 C
Cool Current	1.0 A running
Heat Current	1.0 A running
Fan Current	0.6A running

shop our product catalog

commercial products

industrial products

residential products

support & resources

contractor pro

literature on demand

feedback

training

helpful links

distributor locator

commercial contractor locator

residential contractor locator

homeowners

