



2255B

## Washing Machine Hoses Braided SS

UPC and NSF approved. CP brass nuts. 3/4" female hose x 3/4" female hose. Inner hose is non-toxic polymer for application where water is 33° up to 174°. Burst pressure 1,000 psi.

| Item No. | Description                        | List  | Qty |
|----------|------------------------------------|-------|-----|
| 2255A    | 5' Braided SS Washing Machine Hose | 13.98 | 12  |
| 2255B    | 6' Braided SS Washing Machine Hose | 16.09 | 12  |



2257A

## Braided SS Delta Style Lav Connectors

UPC and NSF approved. CP brass nuts. Inner hose is non-toxic polymer for application where water is 33° up to 174°. Burst pressure 1,000 psi.

| Item No. | Description                                                | List | Qty |
|----------|------------------------------------------------------------|------|-----|
| 2257A    | 12" Braided SS Delta Supply Hose 3/8"od x 3/8" Compression | 3.33 | 25  |
| 2257B    | 20" Braided SS Delta Supply Hose 3/8"od x 3/8" Compression | 3.93 | 25  |



2258-48

## Braided SS Icemaker Connectors

UPC and NSF approved. CP brass nuts. Inner hose is non-toxic polymer for application where water is 33° up to 174°. Burst pressure 1,000 psi.

| Item No. | Description                                   | List  | Qty |
|----------|-----------------------------------------------|-------|-----|
| 2258-12  | 12" Braided SS Icemaker Hose 1/4"od x 1/4"od  | 8.69  | 10  |
| 2258-48  | 48" Braided SS Icemaker Hose 1/4"od x 1/4"od  | 11.27 | 10  |
| 2258-60  | 60" Braided SS Icemaker Hose 1/4"od x 1/4"od  | 14.07 | 10  |
| 2258-72  | 72" Braided SS Icemaker Hose 1/4"od x 1/4"od  | 16.87 | 10  |
| 2258-120 | 120" Braided SS Icemaker Hose 1/4"od x 1/4"od | 20.40 | 10  |



2259A

## Braided SS Water Heater Connectors

UPC and NSF approved.

| Item No. | Description                                           | List  | Qty |
|----------|-------------------------------------------------------|-------|-----|
| 2259A    | 18" Braided SS Water Heater Connector 3/4"fp x 3/4"fp | 12.07 | 25  |
| 2259B    | 24" Braided SS Water Heater Connector 3/4"fp x 3/4"fp | 13.18 | 25  |



2240

## Display for Braided SS Connectors

Mount on 1/4" peg board. Display measures 20" wide x 13" high and extends out 12" from the wall.

| Item No. | Description                                                 | List  | Qty |
|----------|-------------------------------------------------------------|-------|-----|
| 2240     | Wire rack display for SS connectors with header (1 per box) | 71.11 | 1   |

## Supply Tubes Pex

Supplied with ferrule. Rated at 100 PSI at 180° - NSF listed.

| Item No. | Description                | List | Qty |
|----------|----------------------------|------|-----|
| 1930     | 3/8"od x 12" Pex Lav tubes | 1.00 | 100 |
| 1931     | 3/8"od x 20"               | 1.31 | 100 |
| 1932     | 3/8"od x 30"               | 1.84 | 100 |
| 1933     | 3/8"od x 36"               | 2.20 | 100 |



1930



1934

|      |                                |      |     |
|------|--------------------------------|------|-----|
| 1934 | 3/8"od x 12" Pex Closet tubes  | 1.00 | 100 |
| 1935 | 3/8"od x 20"                   | 1.31 | 100 |
| 1936 | 3/8"od Delrin Compression Ring | .09  | 100 |