

For Commercial & Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Quick'N Easy[®]

Braided Stainless Steel & Nylon Faucet Connectors

Features


- Available in 12", 16", 20", 30" and 36"
(305, 406, 508, 762 and 914mm) lengths
- NSF & IAPMO Listed




Pressure – Temperature

Maximum Temperature: Stainless Steel: 180°F (82°C)
Nylon: 140°F (60°C)

Maximum Pressure: 125psi (8.75 bar)



Stainless Steel



Nylon

*The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

	MODEL	✓ TO SUBMIT	DESCRIPTION	DIMENSIONS		MATERIAL
				A		
				in.	mm	
	381 2BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel
	381 2BSPB		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel w/Polished Brass Finish
	381 2B		3⁄8" OD Compression x 1⁄2" Faucet Connection	12	305	Nylon
	381 6BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	16	406	Stainless Steel
	381 6B		3⁄8" OD Compression x 1⁄2" Faucet Connection	16	406	Nylon
	382 0BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel
	382 0BSPB		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel w/Polished Brass Finish
	382 0B		3⁄8" OD Compression x 1⁄2" Faucet Connection	20	508	Nylon
LEAD FREE	383 0BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	30	762	Stainless Steel
LEAD FREE	383 6BSS		3⁄8" OD Compression x 1⁄2" Faucet Connection	36	914	Stainless Steel
	221 2BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	12	305	Stainless Steel
	221 2B		1⁄2" OD Compression x 1⁄2" Faucet Connection	12	305	Nylon
	221 6BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	16	406	Stainless Steel
	222 0BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	20	508	Stainless Steel
	222 0B		1⁄2" OD Compression x 1⁄2" Faucet Connection	20	508	Nylon
LEAD FREE	223 0BSS		1⁄2" OD Compression x 1⁄2" Faucet Connection	30	762	Stainless Steel
	121 2BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	12	305	Stainless Steel
	121 6BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	16	406	Stainless Steel
	122 0BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	20	508	Stainless Steel
	122 0B		1⁄2" FIPS x 1⁄2" Faucet Connection	20	508	Nylon
LEAD FREE	123 0BSS		1⁄2" FIPS x 1⁄2" Faucet Connection	30	762	Stainless Steel
	F381 2BSS		3⁄8" OD Flare x 1⁄2" Faucet Connection	12	305	Stainless Steel
	F382 0BSS		3⁄8" OD Flare x 1⁄2" Faucet Connection	20	508	Stainless Steel
	F38 20B		3⁄8" OD Flare x 1⁄2" Faucet Connection	20	508	Nylon
	381 2SSD		3⁄8" OD Compression x 3⁄8" copper tube Delta connector	12	305	Stainless Steel
	382 0SSD		3⁄8" OD Compression x 3⁄8" copper tube Delta connector	20	508	Stainless Steel
	381 2WSS		3⁄8" OD Compression x 3⁄8" OD Compression	12	305	Stainless Steel
	382 0WSS		3⁄8" OD Compression x 3⁄8" OD Compression	20	508	Stainless Steel

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com

Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca

ES-WB&T-FlxblCntrs-Faucet 0933



A Watts Water Technologies Company

© 2009 Watts