

HEAT PROOF GREASE

VALVE STEM GREASE

HPG-SPEC

PRODUCT DESCRIPTION

PRODUCT

HEAT PROOF GREASE Valve Stem Grease.

TYPE

HEAT PROOF GREASE is a waterproof, nontoxic, high temperature, amber colored, general purpose grease.

Specially formulated for use on all metal faucet and valve stems carrying air, steam and hot or cold water.

Prevents sticking and rust. Assures free movement and extended life.

RECOMMENDED USES

HEAT PROOF GREASE can be used for lubricating valve stems of faucets, valves, ballcocks, plungers, packings, washers or anywhere a water resistant grease is required.

PHYSICAL PROPERTIES

Flash Point, COC: 450°F (232°C)
Melting Temperature: 350°F (176°C)

COLOR/CONSISTENCY

Amber paste.

PACKAGING

U.S. Measure:

<u>Stock Code</u>	<u>Size</u>
HPG2	2 oz. (56.7g)

WEIGHT PER U.S. GALLON

7.4 lbs. (3.4 kg) ± 0.2

SHIPPING WEIGHT PER CASE

<u>Stock#</u>	<u>Case Weight</u>	<u>#/Case</u>
HPG2	5 lbs. (2.3 kg)	24/case

ENVIRONMENTAL STATEMENT

Can be used on potable water since it is safe and nontoxic.

DIRECTIONS FOR USE

VALVE BODIES:

1. Unscrew valve bonnet nut.
2. Rotate valve stem counter clockwise to remove the valve body.
3. Clean stem and threads if necessary.
4. Apply a liberal amount of **HEAT PROOF GREASE** to the stem and stem threads.
5. Reassemble in reverse order. Tighten bonnet nut lightly. Retighten if there is seepage when system pressure is restored.

BALLCOCK AND FLOAT LINKAGES:

1. Clean and descale if necessary.
2. Apply liberal amounts of **HEAT PROOF GREASE** to all rubbing and pivoting surfaces.
3. Apply a thin film of **HEAT PROOF GREASE** to all metal parts in contact with water to prevent corrosion and scale build up.
4. Apply **HEAT PROOF GREASE** to float linkage threads to prevent corrosion.

HPG-SPEC

© 2013 J.C. Whitlam Manufacturing Company
This product is manufactured in the U.S.A.



P.O. Box 380
Wadsworth, Ohio 44282
Phone: 330-334-2524
Fax: 330-334-3005
Email: info@jcwhitlam.com
Website: www.joinpipe.com